


Standart Features

- Steel construction body
- Pneumatic clutch and brake combination
- Adjustable stroke
- Eccentric Crankschaft was made filling
- Liner washer system in connecting rod
- Central lubrication system
- Adjustable rear slides
- 4 guide ram
- Ram adjustment with ratchet system
- Mechanical disc overload protection system
- Gear box welded to body
- Gears closed system in oil
- Maint table with T slots
- Additional table with T slots
- Material and scrap Groove
- Manuel Hand Pump
- Foot paddle
- Double hand control
- Single-continous-interrupted shot - feeding mode options
- PLC applied
- 7" Operator Panel
- 3 Color Warning Light
- Security PLC
- Compliance with CE directives
- Safety light curtains
- Press safety valve
- Pneumatic ram balancing cylinders

Optional Features

- Electric and Timed Automatic
- Grease Lubrication System
- Speed Control Unit

	Value	Unit
Capacity	40	Ton
Throat Depth	210	mm
Table - Ram Distance	300	mm
Additional Table - Ram Distance	210	mm
Housing Width	350	mm
Ram Adjusment	55	mm
Press Width	1220	mm
Press Height	2190	mm
Press Depth	1340	mm
Table Hole Diameter	Ø145	mm
Table Depth	420	mm
Table Width	620	mm
Die Tie Hole Diameter	Ø35	mm
Ram Face Size	300 × 195	mm
Table Height From Floor	660	mm
Stroke	10-70	mm
Strok Per Minute	72	spm
Motor Power	4	kW
Motor Speed	1500	rpm
Approximate Weight	2250	kg

A3	ISO 128	HP_40_PK_AEP_MS	Technical Specifications		Page
TASARIM / DESIGNED	Taha Canat	08.05.2014			1/1
ÇİZEN / DRAWN	Taha Canat	17.10.2025			
KONTROL / CHECKED					
HICO MACHINERY AND ENGINEERING LTD. CO. reserves the right to make changes in dimensions without prior notice.					